

Getting a Child Object by Name from a Parent Object

Orx provides a pair of functions for finding objects in an object hierarchy by name. The two functions are `orxObject_FindChild` and `orxObject_FindOwnedChild`. These functions will filter out any camera or spawner and retrieve the child matching the provided path.

Paths

Paths are composed by object names separated by `..`. A wildcard can be used `*` instead of a name to find children at any depth inside the hierarchy, using depth-first search. Lastly, C subscript syntax, `[N]`, can be used to access the N+1th (indices are 0-based) object matching the path until there.

For example:

- `orxObject_FindChild(pstObject, "Higher.Lower");` will find the first child named Lower of the first child named Higher of `pstObject`
- `orxObject_FindChild(pstObject, "Higher.*.Deep");` will find the first object named Deep at any depth (depth-first search) under the first child named Higher of `pstObject`
- `orxObject_FindChild(pstObject, ".*.Other[2]");` will find the third object named Other at any depth under `pstObject` (depth-first search)
- `orxObject_FindChild(pstObject, "Higher.[1]");` will find the second child (no matter its name) of the first child named Higher of `pstObject`

From:

<https://wiki.orx-project.org/> - **Orx Learning**

Permanent link:

https://wiki.orx-project.org/en/examples/objects/get_child_object_by_name

Last update: **2024/04/20 16:47 (12 months ago)**

